



WATCHMAN WXL2 TECHNICAL SPECIFICATIONS



WXL2
Pedestal Mount

WXL2
Surface Mount



ONE STEP NETWORK CONNECTIVITY
Does not support external cameras

powered by: 

Specifications

Internal HD Camera angles:

Horizontal: 120°
Vertical: 64°
Camera MP: 3MP

Power Consumption

Hardware: 625mA (average)

Wiegand Input Retrofit Part Numbers

Part #s Required:
Mounting plate (supports up to two expansion boards) p/n: CB-WIM 4000
Expansion board (order one or two as required) p/n: CB-WIM 2000

3 Relays:

Switching voltage: 30v
Switching current: 5A

3 Digital Inputs

IP65 - outdoor rated

Operating Temperature

-20°C - 55°C | -4°F - 131°F

Dimensions - Surface Mount

Height- 375mm (14.75")
Width- 305mm (12.75")
Depth - 95mm (3.75")

Dimensions - Pedestal Mount

Height- 375mm (14.75")
Width- 305mm (12.75")
Depth- 95mm (3.75") - Bottom
152mm (6") - Top

All electronics are mounted inside, no external box/wiring needed.

Internet - one step network connectivity

VoIP (no additional service required)
Full-time IP connection

Included in box

Watchman WXL2
Power supply - 5A
Magnetic switch
Installation manual & user manual

Flush Mount Kits (Surface Mount Model)

ENC-WFM1003 includes trim ring and rough-in box (no antennas included)
ENC-WFM1004 includes trim ring (no rough-in box and no antennas included)
ENC-WFM1005 includes trim ring, L-bracket, antennas, rough-in box
ENC-WFM1006 includes trim ring, L-bracket antennas (no rough-in box)