by)**∦**(cellgate

Our readers easily integrate with any CellGate product, providing a Total Property Wireless Access solution.

Powered by:









- Supports Bluetooth, RFID and QR codes for visitor management (varies by reader chosen)
- Touchless entry with CR-INFINITY & CR-READER
 - Integrated CR credentials available





Simple to Install

The CG Installer app easily provisions and changes settings for each reader.





- QR Code Camera
- Bluetooth 5.0
- 125kHz & Encrypted 13.56Mhz, DESFire® EV3
- Proximity card
- Keypad
- 26 Bit Wiegand support
- Front panel: Toughened Glass

- Frame: Aluminum Alloy
- 12 Volt DC connection
- IK07
- Dimensions: 50 x 140 x 26.7 (mm)
- Working Humidity: 10 ~ 90 no condensing
- Working Temperature: -20 C ~ + 55 C

CR-READER Key Features

CR-INFINITY Key Features

- Bluetooth 5.0
- 125kHz & Encrypted 13.56Mhz, DESFire® EV3
- Proximity card
- 26 Bit Wiegand support

((cellgate

- Front panel: Toughened Glass
- Frame: Aluminum Alloy

- 12 Volt DC connection
- IP65
- IK07
- Dimension: 86 x 86 x 33 (mm)
- Working Humidity: 10 ~ 90 no condensing
- Working Temperature: -20 C ~ + 55 C







- 125kHz & Encrypted 13.56Mhz, DESFire® EV3
- Proximity card
- Keypad
- 26 Bit Wiegand support
- Front Panel: Toughened Glass
- Frame: Aluminum Alloy

- 12 Volt DC connection
- IP65
- IK07
- Dimension: 86 x 86 x 33 (mm)
- Working Humidity: 10 ~ 90 no condensing
- Working Temperature: -20 C ~ + 55 C

Cellgate Total Property Wireless Access

